DERWENT- 2

2003-883257

ACC-NO:

DERWENT-

200382

WEEK:

COPYRIGHT 2007 DERWENT INFORMATION LTD

ተቸጥኒድ •

Sewing method of thick material e.g. wadded cloth used as trim cover, makes waste stitch closer to edge and lock stitch on inner side of the

waste stitch

PRIORITY-DATA: 2002JP-0027684 (February 5, 2002)

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE PAGES MAIN-IPC

JP 2003225486 A August 12, 2003 N/A

005 D05B 035/10

INT-CL (IPC): D05B035/10

ABSTRACTED-PUB-NO: JP2003225486A

BASIC-ABSTRACT:

NOVELTY - A waste stitch (21) with a narrow sewing margin (B) is made by machine sewing of overlapped cloths (X,Y). A lock stitch (22) is formed along the inner side of waste stitch with a wider sewing margin (A).

USE - For wadded thick cloth used as trim cover.

ADVANTAGE - Enables reducing sewing margin, hence better fitting of trim **cover** after sewing is enabled, as the **double seam** compresses the evaded cloth.

DESCRIPTION OF DRAWING(S) - The figure is a sectional view of the sewn thick cloth.

waste stitch 21

lock stitch 22

wider sewing margin A

narrow sewing margin B

thick cloth to be sewn X, Y